



TECTROL SUPER TRUCK PLUS XL 530

XL premium low-viscosity engine oil for highly loaded diesel engines of utility vehicles with and without exhaust gas treatment systems



TECTROL SUPER TRUCK PLUS XL 530 is a premium low-viscosity engine oil for highly loaded state-of-the-art diesel engines of utility vehicles with and without exhaust gas treatment systems.

TECTROL SUPERTRUCK PLUS XL 530 is based on state-of-the-art base oils in combination with innovative XL additive technology. This technology leads to significant improvements in the areas of fuel consumption, turbocharger deposits, low-temperature performance and oil consumption.

The XL additive technology of TECTROL SUPER TRUCK PLUS XL 530 (low SAPS) reduces the heavy-metal content in the engine oil. This leads to a significantly lower load on exhaust gas treatment systems such as particulate filters or catalytic converters. In addition, it ensures extremely high cleanliness of the engine and the parts lubricated with oil.

TECTROL SUPER TRUCK PLUS XL 530 provides maximum reliability at minimum consumption!

Benefit	Use
XL technology	Up to 27% less oil consumption, reduction of operating costs
XL technology	Up to 23% enhanced temperature performance, extremely good cold start capability
XL technology	Up to 11% fewer deposits on turbochargers
Excellent wear protection	Perfect lubrication reliability protects the parts and minimizes maintenance costs
Low SAPS content	Excellent protection against deposits and sludge accumulation

Issuing body;
BayWa AG, München
 Energie
 Technical Purchasing Lubricants
 Telephone: +49 89 288511-766

The energy segment of BayWa AG is certified
DIN EN ISO 9001: 2008
This certificate guarantees a consistently high quality standard throughout the supply chain from manufacturers and retailers all the way to consumers.

All data and information is provided based on our current level of knowledge as of: 25.02.15
 Any previous versions are invalid. Subject to change without notice. For further details and information, please visit www.tectrol.de.



TECTROL SUPER TRUCK PLUS XL 530

XL premium low-viscosity engine oil for highly loaded diesel engines of utility vehicles with and without exhaust gas treatment systems



Performance profile (tried and tested in units with fluid specifications)
Viscosity
SAE 5W-30
Approvals
MAN M 3477 MB-Approval 228.51
Specifications
ACEA E6
Recommendations for use
ACEA E7 Deutz DQC IV-10 LA MACK EO-N MTU Oil category 3.1 Renault RLD-2/RXD Volvo VDS-3
Instructions for use
We recommend observing the aggregate manufacturer's instructions.

Product Information

Issuing body;
BayWa AG, München
Energie
Technical Purchasing Lubricants
Telephone: +49 89 288511-766

The energy segment of BayWa AG is certified

DIN EN ISO 9001: 2008
This certificate guarantees a consistently high quality standard throughout the supply chain from manufacturers and retailers all the way to consumers.

All data and information is provided based on our current level of knowledge as of: 25.02.15
Any previous versions are invalid. Subject to change without notice. For further details and information, please visit www.tectrol.de.

TECTROL SUPER TRUCK PLUS XL 530

XL premium low-viscosity engine oil for highly loaded diesel engines of utility vehicles with and without exhaust gas treatment systems



Specifications (average values)		
Specific value	Typical value	Test method
kinematic viscosity at 40°C	69 mm ² /s	DIN 51 562 - 1
kinematic viscosity at 100°C	11.0 mm ² /s	DIN 51 562 - 1
HTHS viscosity	>2.9 (unit_mPas)	CEC-L-36-90
viscosity index	168	DIN ISO 2909
density at 15°C	0.853 g/ml	DIN 51 757
pourpoint	-39 °C	DIN ISO 3016
flash point	228 °C	DIN ISO 2592
sulphate ash	<1.0 M-%	ASTM D 874
base number (TBN)	10 mg K-H/g	DIN ISO 3771

Issuing body;
BayWa AG, München
Energie
Technical Purchasing Lubricants
Telephone: +49 89 288511-766

The energy segment of BayWa AG is certified

DIN EN ISO 9001: 2008

This certificate guarantees a consistently high quality standard throughout the supply chain from manufacturers and retailers all the way to consumers.

All data and information is provided based on our current level of knowledge as of: 25.02.15
 Any previous versions are invalid. Subject to change without notice. For further details and information, please visit www.tectrol.de.